

型号	额定容量 (KVA)	损耗		阻抗 电压 (%)	空载 电流 (%)	重量(kg)			尺寸(mm)			轨距(mm)	
		空载 (W)	负载 (W)			器身	油重	总重	L	W	H	D	E
S9-10/10	10	65	260	4.0	2.8	105	45	180	920	600	930	400	550
S9-20/10	20	100	480		2.4	140	55	230	940	600	980	400	550
S9-30/10	30	130	600		2.1	180	70	300	950	700	1050	400	550
S9-50/10	50	170	870		2.0	245	80	390	1020	790	1110	400	550
S9-63/10	63	200	1040		1.9	275	90	440	1000	790	1150	400	550
S9-80/10	80	250	1250		1.8	325	100	500	1080	800	1150	400	550
S9-100/10	100	290	1500		1.6	360	110	560	1110	820	1240	400	550
S9-125/10	125	340	1800		1.5	415	120	650	1150	820	1250	400	550
S9-160/10	160	400	2200		1.4	490	135	740	1300	830	1320	550	550
S9-200/10	200	480	2600		1.3	570	160	880	1420	860	1360	550	550
S9-250/10	250	560	3050		1.2	705	190	1070	1430	1020	1430	550	650
S9-315/10	315	670	3650		1.1	840	220	1250	1620	1020	1460	550	650
S9-400/10	400	800	4300		1.0	975	290	1510	1820	1060	1550	550	750
S9-500/10	500	960	5100		1.0	1140	335	1760	1520	1070	1620	660	750
S9-630/10	630	1200	6200		4.5	0.6	1310	385	2030	1685	1410	1740	600
S9-800/10	800	1400	7500	0.8		1665	450	2550	1975	1335	1940	600	850
S9-1000/10	1000	1700	10300	0.7		1820	525	2910	2000	1340	1990	820	850
S9-1250/10	1250	1950	12000	0.6		2160	605	3460	2065	1350	2060	820	850
S9-1600/10	1600	2400	145000	0.6		2560	700	4060	2130	1385	2130	820	900
S9-2000/10	2000	2800	17800	0.6		2840	760	4490	2610	1500	2190	820	820