









XCK-M型系列

XCK-M	XCK-M model metal three line incoming mouths.					
	83 8410	Metal head direct-acting type	Steel-roller direct-acting type	Thermoplastic roller tumbler direct-acting type. Single direction with horizontal movement.	Thermoplastic roller tumbler direct-acting type	Multidirection
 <p>2-pole contact terminal Quick off</p>  <p>2-pole contact terminal Slow off</p>						
Machine life (million times)	15	15	15	15	15	10
(m/s) Motion speed (m/s)	1	0.5	1	1	1	1.5
Protection degree	IP665					
Rated work characters	ALTIPAK AC 15; A 300 (U _e =240V U _e =3A) ALTIVAR DC 13; Q 300 (U _e =250V U _e =0.27A)					
Boundary dimensions: width × depth × height	63 × 30 × 64					
Complete switch (2 poles 1-close+1-open, quick)	XCK-M110 ⇄	XCK-M102 ⇄	XCK-M121 ⇄	XCK-M115 ⇄	XCK-M106 ⇄	
Complete switch (2 poles 1-close+1-open, Cut off at first, then connect, cut off slowly)	XCK-M510 ⇄	XCK-M502 ⇄	XCK-M521 ⇄	XCK-M515 ⇄		
Shell (2 poles 1-close+1-open, quick)	ZCK-M1 ⇄	ZCK-M1 ⇄	ZCK-M1 ⇄	ZCK-M1 ⇄	ZCK-M1 ⇄	
Shell (2 poles 1-close+1-open, Cut off at first, then connect, cut off slowly)	ZCK-M5 ⇄	ZCK-M5 ⇄	ZCK-M5 ⇄	ZCK-M5 ⇄	ZCK-M5 ⇄	
Working head: (include executor)	ZCK-D10 ⇄	ZCK-D02 ⇄	ZCK-D21 ⇄	ZCK-D15 ⇄	ZCK-D06	