

Nylon Cable Tie

Application

The nylon binding tie is applied to bunch up various lines together or reinforce one item to another item. It is made of nylon 66(UL approved) of high fire-resistance, which is grade 94V-2. The tie has specialites of antiacid, alkaline-proof & is difficult to be loosened.



Technical specification

Type	Length (mm)	Width (mm)	Type	Length (mm)	Width (mm)
60 × 3	60	3	250 × 5	250	5
80 × 3	80	3	250 × 8	250	8
100 × 3	100	3	300 × 5	300	5
120 × 3	120	3	300 × 8	300	8
150 × 3	150	3	350 × 5	350	5
150 × 4	150	4	350 × 8	350	8
150 × 8	150	8	380 × 6	380	6
180 × 4	180	4	400 × 8	400	8
180 × 8	180	8	450 × 10	450	10
200 × 4	200	4	500 × 10	500	10
200 × 5	200	5	600 × 10	600	10
200 × 8	200	8	650 × 12	650	12

Insulating Connector

Technical specification



Values	Style					
	SM-25	SM-30	SM-35	SM-40	SM-51	SM-76
Tensile strength (lbs)	500	550	600	650	1000	1500
Tongue strength (ft lbs)	6	8	10	10	20	40
Voltage withstand (kv)	6	8	10	12	15	25
Screw (mm)	6	8	8	8	8	10
Weight (g)	28	44	50	86	83	233